





## Surface-mounted downlight

8 320 056 029

5 × 2,5 W, 744 lm, 3000 K warm white,  
linear beam spread 46° / 6°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, with grub screw, ceiling mount: 3 drilled holes  $\varnothing$  5 mm on circular pitch  $\varnothing$  84 mm, cable gland:  $\varnothing$  4-11 mm UP, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral control gear, CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 46° / 6°, luminous flux: 744 lm, wattage: 13 W, delivered lumens 59 lm/W, protection type IP65, protection class I, impact resistance IK08, dimensions (L×H×W): 110 × 85 × 90 mm, weight 2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.

CE   IP65 IK08

## Specification

|                       |                    |                             |                  |
|-----------------------|--------------------|-----------------------------|------------------|
| Wattage               | 13 W               | Beam angle (FWHM)           | 46° / 6°         |
| Delivered lumens      | 59 lm/W            | Housing colour              | silver grey      |
| Light source          | LED 3000 K         | Protection type             | IP65             |
| Color Rendering Index | CRI > 80           | Protection class            | I                |
| Colour tolerance      | max 2 SDCM         | Impact resistance           | IK08             |
| Lifetime ta 25° C     | L90/B10 > 50.000 h | Dimensions                  | 110 × 85 × 90 mm |
| Control gear          | on / off           | Weight                      | 2,00 kg          |
| Input voltage AC      | 205 – 253 V        | Max. ambient temperature ta | 40°              |