


## Uplight 280

8 603 112 009

For und ceramic metal halide lamps (HIT-CE)



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing of corrosion-resistant die-cast aluminum AlSi12, double polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass flush with frame, anti-reflective coating from 1 side, with slip resistant glass (R13 according to DIN EN 51130), for loads up to max. 5000 kg (according to IEC / EN 60598-2-13), silicon gasket, Cover and closure by 6 stainless steel screws, cable gland: M20, connecting terminal: 3 pole, rotationally symmetrical aluminum reflector, tilt range: 0-25, 0,8 m cable Ho7RN-F3G1,5, integral ballast and ignitor, Beam angle (FWHM): 24°, luminous flux: 6600 lm, wattage: 70 W, delivered lumens 80 lm/W, protection type IP67, protection class I, impact resistance IK10, dimensions: Ø 280 mm, width 354 mm, weight 9.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP67 IK10

## Specification

|                  |          |                    |                        |
|------------------|----------|--------------------|------------------------|
| Wattage          | 70 W     | Beam angle (FWHM)  | 24°                    |
| Delivered lumens | 80 lm/W  | Housing colour     | black RAL 7021         |
| Control gear     | on / off | Power supply cable | Ø 6 – 13 mm            |
|                  |          | Protection type    | IP67                   |
|                  |          | Protection class   | I                      |
|                  |          | Impact resistance  | IK10                   |
|                  |          | Dimensions         | Ø 280 mm, width 354 mm |
|                  |          | Weight             | 9,70 kg                |