



Ecoline Mini

8 766 946 009

3 × 1,8 W, 293 lm, 3000 K warm white,
wall washer 20° / 88°

L₁ = 444 mm, L₂ = 407 mm



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of extruded aluminum and corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, polycarbonate cover, with partial frosting for uniform light diffraction, silicon gasket, mounting flanges: 2 elongated holes Ø 6.5, spacing L₂, tilt range: 220°, cable gland:

M16 with 1 m cable Ho5RN-F3G1, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L₉₀/B₁₀ > 50.000 h, Beam angle (FWHM): 20° / 88°, luminous flux: 293 lm, wattage: 5 W, delivered lumens 59 lm/W, protection type IP65, protection class I, impact resistance IK10, windage area 0,017 m², dimensions (L×H×W): 444 × 43 × 40 mm, weight 1.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK10

Specification

Wattage	5 W	Beam angle (FWHM)	20° / 88°
Delivered lumens	59 lm/W	Housing colour	black RAL 7021
Light source	LED 3000 K	Power supply cable	Ø 5 – 9 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L ₉₀ /B ₁₀ > 50.000 h	Impact resistance	IK10
Control gear	on / off	Windage area	0,017m ²
Input voltage AC	220 – 240 V	Dimensions	444 × 43 × 40 mm
Input voltage DC	195 – 240 V	Weight	1,10 kg
Voltage protection	2 kV L/N 4 kV L/PE	Max. ambient temperature ta	50°
Luminaires per B16A / C16A	50 / 85		