


Metaspace

8 215 357 199

6 × 8,6 W, 2700 K warm white, DALI,
Street Optic



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminaire for poles \varnothing 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho7RN-F5G1, connecting terminal: 5 pole, PMMA Linsen, integral driver (DALI), wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	0 W	Housing colour	silver grey
Light source	LED 2700 K	Protection type	IP65
Control gear	DALI	Protection class	I
		Impact resistance	IK08
		Weight	5,00 kg