




Metaspot 3

8 243 249 059

49 W, 1937 lm, RGBW (3000 K) warm white, DMX, wide beam 57°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, for installation on poles \varnothing 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes \varnothing 9 mm, spacing 95 mm, 1 centre hole \varnothing 40 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 6 pole, light source completely shielded, high gloss aluminium reflector, integral driver (AC/DC), Beam angle (FWHM): 57°, luminous flux: 1937 lm, wattage: 49 W, delivered lumens 40 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m², dimensions: \varnothing 201 mm, width 272 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	49 W	Beam angle (FWHM)	57°
Delivered lumens	40 lm/W	Housing colour	black RAL 7021
Light source	LED RGBW (3000 K)	Power supply cable	\varnothing 6 – 11 mm
Control gear	DMX	Protection type	IP65
Input voltage AC	120 – 277 V	Protection class	I
Input voltage DC	120 – 250 V	Impact resistance	IK08
Luminaires per B16A / C16A	22 / 22	Windage area	0,055m ²
		Dimensions	\varnothing 201 mm, width 272 mm
		Weight	5,00 kg
		Max. ambient temperature ta	35°