



Metaspot 2

8 246 267 189

35 W, 3299 lm, 2700 K warm white, DALI,
Street Optic 51° / 141°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, for installation on poles Ø 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes Ø 9 mm, spacing 95 mm, 1 centre hole Ø 40 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral, dimmable driver (DALI), CRI > 80, 3, service life L90/B10 > 50.000 h, Beam angle (FWHM): 51° / 141°, luminous flux: 3299 lm, wattage: 35 W, delivered lumens 96 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,042 m², dimensions: Ø 176 mm, width 244 mm, weight 3.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	35 W	Beam angle (FWHM)	51° / 141°
Delivered lumens	96 lm/W	Housing colour	white RAL 9002
Light source	LED 2700 K	Power supply cable	Ø 6 - 11 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	3	Protection class	II
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,042m ²
		Dimensions	Ø 176 mm, width 244 mm
		Weight	3,70 kg
		Max. ambient temperature ta	45°