





## Monospot 4

8 904 042 159

46 W, 2703 lm, 2700 K – 6500 K tunable white DALI, wide beam 57°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, Colour: black RAL 7021, dark screenprint, silicon gasket, closure with 3 stainless steel screws, bracket: 2 long holes Ø 7 mm, spacing 40-60 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, highly efficient faceted rotationally symmetrical reflector, integral, dimmable driver (DALI), CRI > 80 / >70, Beam angle (FWHM): 57°, luminous flux: 2703 lm, wattage: 46 W, delivered lumens 59 – 74 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,075 m<sup>2</sup>, dimensions: Ø 210 mm, width 240 mm, weight 4.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP67 IK08

## Specification

Wattage	46 W	Beam angle (FWHM)	57°
Delivered lumens	59 – 74 lm/W	Housing colour	black RAL 7021
Light source	LED 2700 K – 6500 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80 / >70	Protection type	IP67
Control gear	DALI	Protection class	I
		Impact resistance	IK08
		Windage area	0,075m <sup>2</sup>
		Dimensions	Ø 210 mm, width 240 mm
		Weight	4,80 kg
		Max. ambient temperature ta	35°