




Superlight Compact Micro

8 813 045 329

5 × 2,5 W, 796 lm, 4000 K neutral white, DALI / 1-10V, linear vertical 46° / 6°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of die-cast aluminum ALSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 2 drilled holes \varnothing 8.5 mm, spacing 70 mm, 1 centre hole \varnothing 17 mm, tilt range: 120°, cable gland: M16, connecting terminal: 5 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (DALI / 1-10 V), CRI > 80, max 2 SDCM, service life $L_{90/B_{10}} > 50.000$ h, Beam angle (FWHM): 46° / 6°, luminous flux: 796 lm, wattage: 13 W, delivered lumens 64 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,011 m², dimensions (L×H×W): 110 × 85 × 90 mm, weight 1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



Specification

Wattage	13 W	Beam angle (FWHM)	46° / 6°
Delivered lumens	64 lm/W	Housing colour	black RAL 7021
Light source	LED 4000 K	Power supply cable	\varnothing 5 – 9 mm
Color Rendering Index	CRI > 80	Protection type	IP67
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	$L_{90/B_{10}} > 50.000$ h	Impact resistance	IK08
Control gear	DALI / 1-10V	Windage area	0,011 m ²
Input voltage AC	200 – 255 V	Dimensions	110 × 85 × 90 mm
Voltage protection	3 kV L/N 3 kV L/PE	Weight	1,00 kg
		Max. ambient temperature ta	45°